

RECHARGEABLE SEALED LEAD ACID BATTERY

SPECIFICATION

MP12-12C (Artikel-Nr. 2003924)

Nominal Voltage (V) 12V

Nominal Capacity

20 hour rate	(0.6A	to	10.50V)	12.00Ah
10 hour rate	(1.14A	to	10.50V)	11.40Ah
5 hour rate	(2.04A	to	10.20V)	10.20Ah
1 C	(12A	to	9.60V)	6.80Ah
3 C	(36A	to	9.60V)	4.80Ah

Weight Approx. 4.02kg (8.84lbs)

Internal Resistance (at 1KHz) Approx. 11 mΩ

Maximum Discharge Current for

5 seconds: 180A

Charging Methods at 25°C (77°F)

Cycle use:	
Charging Voltage	14.70V to 14.80V
Coefficient -5.0mV/°C/cell	
Maximum Charging Current:	3.6A
Standby use:	
Float Charging Voltage	13.50V to 13.80V
Coefficient -3.0mV/°C/cell	

Operating Temperature Range




Charge	-15°C (5°F)	to	40°C (104°F)
Discharge	-15°C (5°F)	to	50°C (122°F)
Storage	-15°C (5°F)	to	40°C (104°F)

Charge Retention (shelf life) at 20°C (68°F)

1 month	92%
3 month	90%
6 month	80%


Case Material ABS
(UL94 HB flame retardant case / cover)

Terminal F2 (Faston Tab 250)




CHARACTERISTIC & PERFORMANCE DATA


Effect of Temperature on Capacity 25°C (77°F)




Capacity Retention Characteristic



Trickle (or float) Service Life



Cycle Service Life



- PERFORMANCE DATA

Discharge Rates in Watts to Various End Voltages at 25°C (77°F)

End Voltage		1.85V	1.80V	1.75V	1.70V	1.67V	1.65V	1.60V
Time								
5	min	463	505	536	569	584	598	627
10	min	339	362	378	392	397	405	413
15	min	253	272	283	291	295	299	306
30	min	160	168	174	180	182	184	187
60	min	89.5	95.2	100	103	104	105	106
120	min	46.8	51.6	54.1	55.3	55.7	56.3	57.1
180	min	32.4	36.9	39.2	40.1	41.8	42.6	43.2
240	min	26.6	29.8	31.3	32.2	32.6	33.1	33.7
300	min	24.7	26.1	27.1	27.9	28.3	28.6	29.0
600	min	14.6	15.3	15.7	16.0	16.1	16.2	16.3
1200	min	7.77	7.86	8.10	8.22	8.31	8.41	8.59

- Discharge Rates in Amperes to Various End Voltages at 25°C (77°F)

End Voltage		1.85V	1.80V	1.75V	1.70V	1.67V	1.65V	1.60V
Time								
5	min	37.8	41.8	44.6	47.5	48.8	50.1	52.7
10	min	28.1	30.3	31.5	32.7	33.2	33.8	34.6
15	min	21.3	22.6	23.7	24.6	25.0	25.4	26.1
30	min	12.6	13.5	14.1	14.6	14.8	15.0	15.3
60	min	8.55	8.74	8.86	8.97	9.02	9.08	9.16
120	min	4.71	4.84	4.95	5.04	5.08	5.13	5.18
180	min	3.14	3.33	3.40	3.46	3.49	3.52	3.56
240	min	2.15	2.26	2.35	2.42	2.45	2.49	2.74
300	min	1.98	2.06	2.12	2.18	2.20	2.23	2.27
600	min	1.19	1.22	1.24	1.26	1.27	1.28	1.29
1200	min	0.619	0.626	0.645	0.654	0.661	0.669	0.683

All data on the spec. sheet is an average value:

The tolerance range : $X < 6\text{min}$ (+15%~-15%), $6\text{min} \leq X < 10\text{min}$ (+12%~-12%), $10\text{min} \leq X < 60\text{min}$ (+8%~-8%), $X \geq 60\text{min}$ (+5%~-5%)