




Basic Specifications

Voltage:	12 Volt
Capacity:	20 hour rate: 4Ah 10 hour rate: 3.9Ah 5 hour rate: 3.55Ah
Design life:	3-5 years
Appr. dimensions:	195x47x70/76mm (LxWxH) (±2mm)
Terminal:	Faston Tab 4.8mm T1
Container & lid:	ABS
Internal Resistance:	45mΩ (Fully charged)
Approximate weight:	1.45kg
Max charge current:	1.26A
Max discharge current:	63A (5 sec.)
Operating temp. range:	-20°C ~ +50°C
Self discharge:	lower than 3% per month

Typical Applications

- Security systemens / Emergency lighting
- UPS / Emergency Power
- Household appliances
- Traffic sensors
- Telecommunication
- Garden tools
- Toys

Discharge data in Watts per battery (25°C)

	(V/cell)	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
End Voltage	1.80V	150	95,5	78,2	45,6	28,8	12,1	8,27	4,59	2,47
	1.75V	159	101	82,6	47,3	29,7	12,5	8,53	4,69	2,52
	1.70V	166	106	85,5	48,5	30,3	12,6	8,58	4,72	2,54
	1.65V	173	110	88,8	50	31,10	12,6	8,64	4,74	2,55
	1.60V	178	114	91	51	31,60	12,7	8,7	4,76	2,56

Discharge data in Amperes (25°C)

	(V/cell)	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
End Voltage	1.80V	13,4	8,47	6,86	3,98	2,49	1,02	0,69	0,38	0,21
	1.75V	14,2	8,97	7,25	4,13	2,57	1,05	0,71	0,39	0,21
	1.70V	14,8	9,37	7,5	4,23	2,62	1,06	0,72	0,39	0,21
	1.65V	15,5	9,78	7,79	4,36	2,69	1,06	0,72	0,39	0,21
	1.60V	16	10,1	7,98	4,45	2,73	1,07	0,73	0,4	0,21


General purpose batteries

With a range of well over 50 models, pbq offers one of the widest selections in the battery industry. The batteries are designed with the cost and quality conscious user in mind offering an excellent price/performance ratio. pbq has a full series of 6 and 12 Volt models available for a wide range of applications and intents to keep this range in production for many years to come. These General Purpose batteries have been designed for a functional life of 4-5 years at an operating temperature of 25°C in a standby application.


Features

- Absorbent Glassmat Technology
- Low self discharge
- Classified as non-spillable and Non Dangerous goods by IATA, FAA, ADR, IMDG
- Can be discharged or stored in any position without leakage
- Cannot be charged while terminal is downward


Design Life




Discharge time VS. discharge current (25°C)



Battery Charging Characteristics



Battery Charging Characteristics



Models available

Model pbq	Capacity in Ah	Dimensions (±2mm) (LxWxH1/H2)	Weight
pbq 3.5-4	3.5	91 x 35 x 64	0.46 kg
pbq 1.2-6	1.2	97 x 24 x 58	0.31 kg
pbq 3.2-6	3.2	134 x 35 x 67	0.71 kg
pbq 4.5-6	4.5	70 x 47 x 107	0.75 kg
pbq 7-6	7	151 x 34 x 100	1.20 kg
pbq 12-6	12	151 x 50 x 100	1.85 kg
pbq 0.8-12	0.8	96 x 25 x 62	0.40 kg
pbq 1.2-12*	1.2	97 x 43 x 58	0.54 kg
pbq 1.3-12	1.3	97 x 48 x 57	0.63 kg
pbq 2.3-12*	2.3	178 x 35 x 67	0.88 kg
pbq 2.3-12C	2.3	182 x 23 x 61	0.73 kg
pbq 2.6-12S	2.6	70 x 48 x 104	0.85 kg
pbq 2.6-12	2.6	178 x 34 x 71	0.92 kg
pbq 2.9-12	2.9	79 x 56 x 105	1.05 kg
pbq 3.2-12*	3.2	134 x 67 x 67	1.30 kg
pbq 3.4-12	3.4	134 x 67 x 67	1.30 kg
pbq 4-12	4	195 x 47 x 76	1.58 kg
pbq 5.2-12	5.2	90 x 70 x 107	1.65 kg
pbq 7-12*	7	151 x 65 x 102	2.20 kg
pbq 7-12L*	7	151 x 65 x 102	2.20 kg
pbq 12-12*	12	151 x 98 x 98	3.75 kg
pbq 18-12*	18	181 x 76 x 167	5.60 kg
pbq 26-12*	26	165 x 176 x 127	9.30 kg
pbq 28-12 T2	28	165 x 125 x 175	8.60 kg
pbq 40-12*	40	197 x 165 x 170	13.5 kg
pbq 65-12*	65	350 x 167 x 186	22.0 kg

* VdS models

Certificates



VdS approved VRLA batteries

The VdS-approved pbq batteries form a special range that has been tested and qualified by the German VdS institute. The concept behind VdS recognition; ensuring tested and certified quality in the products and services being offered in the safety and security markets, is of equally advantageous for user and supplier.

Flame Retardant ABS casing

All VdS models are accomplished in Flame Retardant ABS casing. Due to the right choice of the flame retardant, the batteries remain RoHS Compliant.